



EAAudKit-2

Audio Base Station with Mic-2

Description

Complete single zone audio surveillance system. Can be used independently for monitoring live audio or with VCRs/DVRs for recording and playback.



Kit Includes:

- Pre-Amplified Microphone
- Audio Amplifier
- 12 VDC AC Adapter
- 3' Dual RCA Patch Cable
- Warning Label

Wiring Requirements:

Stranded 22 Gauge, 2 Conductor shielded cable. Distances up to 1000'.

Amplifier Specifications

- Standard RCA jacks for connection to VCRs/DVRs, etc.
- Easy cable run termination.
- 1 Watt power amplifier.
- 3" full range speaker.
- Tape monitor switch.
- 3.5mm headphone jack.
- Power: 12VDC @ 250mA
- Reverse polarity protected and fused.
- Dimensions: W 4.14 x L 5.44 X H 1.52

Microphone Specifications

- Omni-directional Electret element. 25' range in all directions.
- Low noise MOSFET pre-amplifier.
- Line level, unbalances output.
- Adjustable Gain.
- Treble boost circuit. Selectable on/off. Enhances clarity of time lapse recordings.
- Easy cable run termination.
- Flush or surface mountable. Can be mounted on a single gang electrical box.
- Power: 12VDC @ 10mA.

