

# PRODUCT SPECIFICATION



## DDVDN-530

Indoor Day/Night Dome Camera

### Key Features

SONY 1/3" Super HAD CCD sensor  
Sony Digital Signal Processor (DSP) 530 TVL  
3.7-12mm AI Lens  
3 Axis, Dual Voltage  
Surface Mountable  
Service Monitor Output



### Specifications

|                         |   |
|-------------------------|---|
| Image Pick-up Device    | SONY 1/3" interline transfer CCD sensor |
| Effective Pixels        | 768X494                                 |
| Resolution              | 530 TV-Lines, Digital Day/Night         |
| S/N Ratio               | 50dB @ AGC Off                          |
| Min. Illumination       | 0.2 Lux (AGC on) @30IRE                 |
| Auto Electronic Shutter | 1/60s~1/100,000s                        |
| Auto Gain Control       | On/Off                                  |
| Auto White Balance      | Auto (2500 K-9500K)                     |
| Lens                    | 3.7-12mm F1.2 DC iris varifocal         |
| Scanning System         | 2:1 Interlace V:59.95Hz H:15.734KHz     |
| Synchronous System      | Internal/ Line lock selectable          |
| Video Output            | 1Vp-p 75 Ohms, BNC connector            |
| Power                   | 12VDC/24VAC+/-10%                       |
| Operating Temp          | 14F to 122F                             |
| Dimensions              | 4.75"(W)x4.25"(H) 121mm(W)x109mm(H)     |