



## ExitPoint™ Directional Sounder with Voice Messaging

*Triggered by existing fire detection systems, directional sounders positioned at carefully chosen locations guide building occupants along escape routes and to perimeter building exits.*



### Features

- Listed to UL 464 (indoor applications only)
- Designed to effectively guide occupants along escape routes in unfamiliar surroundings or in areas with poor visibility
- Includes five field-selectable power settings
- Reduces evacuation times by as much as 75 percent
- Includes four field-selectable routing evacuation patterns
- Works in open areas, corridors and stairs
- Provides fifteen different language selections
- Provides an optional disable feature for use in conjunction with a control module or heat sensor
- Has a compact design with a low profile

The ExitPoint directional sounder model PF24V has an integral audio amplifier that produces a pulsating sound consisting of broadband low-, mid- and high-range sounds. The broadband noise makes it possible to determine the location of the sound. There are four pulse patterns that can be used to create an egress pathway out of a building and to mark perimeter exits. In addition to the broadband noise, the sounder is capable of playing an alert message in the form of a recorded voice message or other audible signals. These messages instruct occupants of the correct action to take as they approach the directional sounder, and enables them to react quickly and confidently when the sounder is activated. Fifteen different language combinations are available to instruct occupants that they are nearing an exit, a stairway up, a stairway down or an area of refuge. The PF24V directional sounder also incorporates an optional disable feature for use in conjunction with a control module or heat sensor.

The directional sounder features a number of field-selectable power settings, including high, medium-high, medium, medium-low, and low. Its low profile compact design and its ability to flush mount in a 4" x 4" x 2¼" back-box provide installation ease and pleasing aesthetics.

ExitPoint directional sounders, fitted in addition to normal building evacuation sounders, draw people to evacuation routes in both good and poor visibility. The PF24V directional sounder can be used in a wide range of building applications. Trials consistently have shown an improvement of up to 75 percent in evacuation times in smoke and up to 35 percent without smoke. The 2007 Edition of NFPA 72 now provides installation and maintenance guidelines on directional sounders.

### Agency Listings



S4011



3027815



7135-1653:175



492-04-EV.2

## Specifications

Electrical Specifications		Mechanical Specifications	
Voltage Input	Regulated 24 Volts	Input Terminals	12–24 AWG
Operating Voltage Range	16 to 33 Volts	Speaker Size	4" (101 mm)
Operating Temperature	32°F to 120°F (0°C to 49°C)	Grille Size	4 $\frac{7}{8}$ " (127 mm)
Power Setting	High, medium-high, medium, medium-low, and low.		

## Current Draw Measurements and Sound Output Guide

Speed Selection	DIP Switch Selection	Power Setting	Maximum DC Operating Current (mA RMS) (16 to 33V)	Audibility (dBA) (16 to 33V) Note 1	Audibility (dBA) (16 to 33V) Note 2
Fast (Exit)	10	High	185	84	75
Fast (Exit)	10	Med-High	131	81	72
Fast (Exit)	10	Med	78	78	69
Fast (Exit)	10	Med-Low	76	75	66
Fast (Exit)	10	Low	64	72	63
Med-Fast	9	High	170	83	74
Med-Fast	9	Med-High	124	80	71
Med-Fast	9	Med	75	77	68
Med-Fast	9	Med-Low	73	74	65
Med-Fast	9	Low	62	71	62
Med-Slow	8	High	135	82	73
Med-Slow	8	Med-High	104	79	70
Med-Slow	8	Med	67	76	67
Med-Slow	8	Med-Low	65	73	64
Med-Slow	8	Low	57	70	61
Slow	7	High	120	82	72
Slow	7	Med-High	92	79	69
Slow	7	Med	62	76	66
Slow	7	Med-Low	61	73	63
Slow	7	Low	54	70	60

Note 1: Sound output measured in anechoic room at 10 feet.

Note 2: Sound output measured in a reverberant room at 10 feet.

## Power Setting Guide

DIP Switch Position 1 Setting	DIP Switch Position 2 Setting	DIP Switch Position 3 Setting	Power Setting
Off	Off	Off	High
On	Off	Off	Med-High
Off	On	Off	Med
Off	Off	On	Med-Low
On	On	On	Low

## Additional Tone Selection

Switch Position 5 Setting	Switch Position 6 Setting	Sound Output
On	On	Area of Refuge
On	Off	Stairs Up
Off	On	Stairs Down
Off	Off	Exit Here

## Enable/Disable Selection

Switch Position 4 Setting	Terminals 3 & 4	Sound Output
On	Open	Disabled
On	Closed	Enabled
Off	Open	Enabled
Off	Closed	Disabled

## Language/audible tone selection guide

Rotary Switch Selection	Tone/Language
0	Audible tone/sweep
1	English
2	Spanish
3	French
4	English/Spanish
5	English/French
6	Korean
7	Cantonese
8	Mandarin
9	English/Cantonese
10	English/Mandarin
11	Cantonese/Mandarin
12	English/Korean
13	English/Portuguese
14	English/Russian
15	English/Polish

## Ordering Information

Part No.	Description
PF24V	ExitPoint™ Directional Sounder with Voice Messaging



3825 Ohio Avenue • St. Charles, IL 60174  
Phone: 800-SENSOR2 • Fax: 630-377-6495

©2009 System Sensor.  
Product specifications subject to change without notice. Visit [systemsensor.com](http://systemsensor.com) for current product information, including the latest version of this data sheet.  
A05-0377-003 • 2/09 • #11995